

CSR-550 DECK STAIN
WATER-BASED ACRYLIC STAIN

DESCRIPTION

CSR-550 DECK STAIN is a premixed water-based acrylic stain in a "ready-to-use" formulation of a high quality butyl acrylic copolymer. Additional modifiers are incorporated to enhance the durability of the acrylic solids and provide ease of application as a pigmented protective sealer over acrylic-modified concrete overlay systems (i.e. CenturyStone Concrete Coatings).

TYPICAL USES

CSR-550 DECK STAIN is an integral component in the CenturyStone Decorative Coating System.

As a stand-alone sealer the CSR-550 DECK STAIN is excellent protection over a newly installed concrete overlay. It will continue to provide protection well after the complete curing of the overlay.

METHODS OF APPLICATION

CSR-550 DECK STAIN is a ready-to-use product that can be applied by roller, brush, broom or industrial sprayer.

PRIMARY FEATURES of CSR-550 DECK STAIN

- High Solids Formula - 30%
- All-purpose COLOR sealer
- Slip-resistant top coat (with resin sand)
- Maintains cool walking surface
- Unlimited Decorative Applications
- Compatible with acrylic-based products
- Minimal drying time
- Suitable for interior or exterior
- Good abrasion resistance
- Good chemical resistance

APPLICATION INSTRUCTIONS

DO NOT DILUTE

Use a clean roller, brush, broom or an industrial sprayer.

AVOID PUDDLING. Immediately brush or roll out puddles from drips, spills or over-spray to avoid build-up of unbonded acrylic solids. Rinse off tools with water immediately after use. Apply CSR-550 DECK STAIN to properly prepared, clean surfaces. For additional slip-resistance apply coat of CSR-700 "Diamond Glaze" with resin sand casted over freshly rolled surfaces. Do not install at ambient temperatures below 50 degrees F.

COVERAGE

300-500 SF/gallon.

PACKAGING

5-gallon bucket
Pallet (36 buckets)

