

CSR-600 "AQUA SHIELD"
WATER-BASED ACRYLIC SEALER

DESCRIPTION

CSR-600 AQUA SHIELD is a premixed water-based acrylic sealer in a "ready-to-use" formulation of a high quality butyl acrylic copolymer. Additional modifiers are incorporated to enhance the durability of the acrylic solids and provide ease of application as a protective sealer over acrylic-modified concrete overlay systems (i.e. CenturyStone Concrete Coatings).

TYPICAL USES

CSR-600 AQUA SHIELD is an integral component in the CenturyStone Concrete Repair and Decorative Coating System.

As a stand-alone sealer the CSR-600 AQUA SHIELD is excellent protection over a newly installed concrete overlay. It will continue to provide protection well after the complete curing of the overlay. Additionally, CSR-600 AQUA SHIELD can serve as a primer for the CSR-700 DIAMOND GLAZE solvent-based acrylic sealer.

METHODS OF APPLICATION

CSR-600 AQUA SHIELD is a ready-to-use product that can be applied by roller, brush, broom or industrial sprayer.

PRIMARY FEATURES of CSR-600 AQUA SHIELD

- High Solids Formula - 30%
- All-purpose sealer
- Slip-resistant top coat (with resin sand)
- Maintains cool walking surface
- Unlimited Decorative Applications
- Compatible with acrylic-based products
- Minimal drying time
- Suitable for interior or exterior
- Good abrasion resistance
- Good chemical resistance

APPLICATION INSTRUCTIONS

DO NOT DILUTE

Use a clean roller, brush, broom or an industrial sprayer.

AVOID PUDDLING. Immediately brush or roll out puddles from drips, spills or over-spray to avoid build-up of unbonded acrylic solids. Rinse off tools with water immediately after use. Apply CSR-600 AQUA SHIELD to properly prepared, clean surfaces. For additional slip-resistance add resin sand by mixing in sealer or casting over freshly rolled surfaces.

Do not install at ambient temperatures below 50 degrees F.

COVERAGE

300-500 SF/gallon.

PACKAGING

5-gallon bucket
Pallet (36 buckets)

